



Wall-mounted radiators with high thermal inertia fluid, programmable digital display, with built-in electronics for remote control (via KIT 1 THERMOWEB, as accessory) from any device connected to the internet.

Characteristics

- Die-cast aluminium structure.
- Die-cast aluminium structure.
- Programming or configuration modes:
 - Comfort mode ☀
Programmable temperature of 10°C - 30°C.
 - Economy mode 🌙
Programmable temperature of 5°C - 19°C.
 - Anti-ice mode ❄️
Programmable temperature of 5°C - 10°C.
 - Extended absence mode 📱
 - Timed configuration ⌚
 - Keypad lock configuration 🔒
 - Consumption meter configuration (kWh) ⚡
 - Configuration detect windows open 🪟
- LCD screen.
- High-precision electronic temperature sensor.
- Thermal bulb protector.
- Daily and weekly schedule.
- Power cable (located at the bottom right rear).
- IP20.
- Class I.



LCD screen



Accessories:
EMI-TECH FEET KIT (2 units)
Plastic feet (not included)

TECHNICAL CHARACTERISTICS

Model	N° components	Power (W)	Voltage 50 Hz (V)	Maximum absorbed current (A)	Weight (kg)	Power cable length (mm)	Dimensions LxWxH (mm)	Colour
EMI-TECH 4 THERMOWEB	4	600	230	2,6	9	1400	420x95x580	White RAL 9010
EMI-TECH 5 THERMOWEB	5	750	230	3,3	11	1400	500x95x580	White RAL 9010
EMI-TECH 6 THERMOWEB	6	900	230	4	13	1400	580x95x580	White RAL 9010
EMI-TECH 8 THERMOWEB	8	1200	230	5,4	17	1400	740x95x580	White RAL 9010
EMI-TECH 10 THERMOWEB	10	1500	230	6,5	20,5	1400	900x95x580	White RAL 9010