




Characteristics

Circular diffusers with adjustable cones on panel for air intake and delivery.
Installation height: 2,7-3,5 m.

Material



External cone in aluminium, central cone and damper (included in the price) in plastic RAL 9010 painted.

Fixing




By using screws (Standard), by clips (on demand).

Accessories

Galvanized steel connecting plenum.
Equalizer (EQ).



Air supply duct



Selection table

Model	Q [m³/h]		L _{WA} [dB(A)]		X _(0,25) -Y _(0,25) [m]		Dp _t [Pa]	
	min.	maks.	min.	maks.	min.	maks.	min.	maks.
200x100	5	25	21	29	1,7	6,7	5	55
300x100	10	40	21	29	1,7	6,7	5	55
400x100	15	55	21	29	1,7	6,7	5	55
500x100	20	70	21	29	1,7	6,7	5	55
600x100	25	85	21	29	1,7	6,7	5	55
700x100	30	100	21	29	1,7	6,7	5	55
800x100	35	115	21	29	1,7	6,7	5	55
1000x100	45	145	21	29	1,7	6,7	5	55
1200x100	55	175	21	29	1,7	6,7	5	55
300x150	25	75	23	32	1,9	6,9	5	55
400x150	30	110	23	32	1,9	6,9	5	55
500x150	40	140	23	32	1,9	6,9	5	55
600x150	50	170	23	32	1,9	6,9	5	55
700x150	60	200	23	32	1,9	6,9	5	55
800x150	70	230	23	32	1,9	6,9	5	55
1000x150	90	290	23	32	1,9	6,9	5	55
1200x150	105	355	23	32	1,9	6,9	5	55
300x200	35	115	25	34	2,1	7,3	5	55
400x200	50	160	25	34	2,1	7,3	5	55
500x200	60	205	25	34	2,1	7,3	5	55
600x200	75	255	25	34	2,1	7,3	5	55
700x200	90	300	25	34	2,1	7,3	5	55
800x200	105	345	25	34	2,1	7,3	5	55
1000x200	130	440	25	34	2,1	7,3	5	55
1200x200	160	530	25	34	2,1	7,3	5	55
400x250	65	215	27	36	2,4	7,7	5	55
500x250	85	275	27	36	2,4	7,7	5	55
600x250	100	340	27	36	2,4	7,7	5	55
700x250	120	400	27	36	2,4	7,7	5	55
800x250	140	460	27	36	2,4	7,7	5	55
1000x250	175	585	27	36	2,4	7,7	5	55
1200x250	210	705	27	36	2,4	7,7	5	55
500x300	105	345	29	38	2,6	7,9	5	55
600x300	125	425	29	38	2,6	7,9	5	55
700x300	150	500	29	38	2,6	7,9	5	55
800x300	175	575	29	38	2,6	7,9	5	55
1000x300	220	730	29	38	2,6	7,9	5	55
1200x300	265	885	29	38	2,6	7,9	5	55