



- Description** Round steel plenum for diffusers DVO, DVD, DVDS, DVOS and DVS. Standard (KO-H-PP-M, KO-V-PP-M) or insulated (KO-H-PP-M-I, KO-V-PP-M-I), with calibration damper and mounting bridge and with equalizer sheet.
- Material** Galvanized sheet metal.
- Utilization** For ceiling installation and for air intake and delivery.
- Fixing** By using screws on the hangers.

Dimensions

Description	A [mm]	ØD [mm]	H [mm]
Plenum box KO-H-PP-M 300/125	290	122	250
Plenum box KO-H-PP-M 300/160	290	157	250
Plenum box KO-H-PP-M 310/125	300	122	250
Plenum box KO-H-PP-M 310/160	300	157	250
Plenum box KO-H-PP-M 400/160	390	157	290
Plenum box KO-H-PP-M 400/200	390	197	290
Plenum box KO-H-PP-M 500/200	490	197	290
Plenum box KO-H-PP-M 500/250	490	247	290
Plenum box KO-H-PP-M 600/200	590	197	340
Plenum box KO-H-PP-M 600/250	590	247	340
Plenum box KO-H-PP-M 625/250	615	247	340
Plenum box KO-H-PP-M 800/315	790	312	400
Plenum box KO-H-PP-M 825/315	815	312	400

*insulation thicknes from 6 mm to 19 mm

Description	A [mm]	ØD [mm]	H [mm]
Plenum box KO-V-PP-M 300/125	290	122	250
Plenum box KO-V-PP-M 300/160	290	157	250
Plenum box KO-V-PP-M 310/125	300	122	250
Plenum box KO-V-PP-M 310/160	300	157	250
Plenum box KO-V-PP-M 400/160	390	157	290
Plenum box KO-V-PP-M 400/200	390	197	290
Plenum box KO-V-PP-M 500/200	490	197	290
Plenum box KO-V-PP-M 500/250	490	247	290
Plenum box KO-V-PP-M 600/200	590	197	340
Plenum box KO-V-PP-M 600/250	590	247	340
Plenum box KO-V-PP-M 625/250	615	247	340
Plenum box KO-V-PP-M 800/315	790	312	400
Plenum box KO-V-PP-M 825/315	815	312	400

*insulation thicknes from 6 mm to 19 mm

Selection key

